



The removable front panels chassis is a 19 inch 1U sliding panel in two parts: one sliding chassis and one front panel, which receives the optical adaptors. The flexibility of its two piece construction allows you to maintain a stock of the chassis and then attach a suitable front panel as required.

Features

- Recessed panel option
- No exposed screws
- Screen printed for easy labelling
- 45° working angle
- Rear cable entry options
- Panel numbers and rack number identification labels
- High quality finish, no sharp edges

Specification

ELEMENT	CHARACTERISTIC
U Size	1U (44.4mm)
Width	482mm
Depth	204mm
Net weight	2.1 kgs
Packaged weight	3 kgs
Packaged dimensions	530mm W X 55mm H x 260mm D
IP rating	IP20
Suitable for Adaptor type	All
Mounting Adjustment range	50mm
Cable entry 20mm	2
Cable entry 25mm	2
Material	Cold- rolled steel
Material thickness	1.2mm
Material coating	Electro Static Powder Coating
Colour	Black RAL 9004 Grey RAL 7035
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN 50173, IEC 60304, IEC 61754, EN 297-1
Compliant to	RoHS, Reach/SVHC