

Part Number: NN00101

Category 3 cable



Product Description

CAT3 (16MHz), 100-pair U/UTP, Premise Horizontal Cable, 24 AWG, HDPE insulation, LSZH jacket

Technical Specifications

Product Overview

Environmental Space:	Outdoor
Suitable Applications:	Backbone cable; Support current and future Category 3 applications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
24	Solid	BC - Bare Copper	0.51 mm	100

Conductor Count:	200
Total Number of Pairs:	100
Conductor Size:	24 AWG

Insulation

Type	Material	Nominal Diameter
Dielectric	Polyethylene	0.88 mm

Color Chart

Number	Color
Pair 1	White & Blue
Pair 2	White & Orange
Pair 3	White & Green
Pair 4	White & Brown
Pair 5	White & Grey
Pair 6	Red & Blue
Pair 7	Red & Orange
Pair 8	Red & Green
Pair 9	Red & Brown
Pair 10	Red & Grey
Pair 11	Black & Blue
Pair 12	Black & Orange
Pair 13	Black & Green
Pair 14	Black & Brown
Pair 15	Black & Grey
Pair 16	Yellow & Blue
Pair 17	Yellow & Orange
Pair 18	Yellow & Green
Pair 19	Yellow & Brown
Pair 20	Yellow & Grey
Pair 21	Violet & Blue
Pair 22	Violet & Orange
Pair 23	Violet & Green
Pair 24	Violet & Brown

Pair 25	Violet & Grey
---------	---------------

Color Chart 2

Number	Color
Unit 1	Blue
Unit 2	Orange
Unit 3	Green
Unit 4	Brown

Outer Jacket Material

Material	Color	Max. Diameter	Min. Wall Thickness	Ripcord
LSZH / FRNC	Gray	22 mm	1.2 mm	Yes

Construction and Dimensions

Cabling

Description
4 units of 25 pairs covered with a polyester foil

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
93.8 Ohm/km	5 %	5 Ohm

Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
330 pF/m	66 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance
100 Ohm	15 Ohm

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. SRL (Structural Return Loss)
0.772 MHz	2.2 dB/100m	45 dB	43 dB	12 dB
1 MHz	2.6 dB/100m	44 dB	41 dB	12 dB
4 MHz	5.6 dB/100m	34 dB	32 dB	12 dB
8 MHz	8.5 dB/100m	29 dB	27 dB	12 dB
10 MHz	9.7 dB/100m	28 dB	26 dB	12 dB
16 MHz	13.1 dB/100m	25 dB	23 dB	10 dB

Current

Max. Recommended Current [A]
1.5 A

Voltage

Voltage Rating [V]
72 V

Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	110 mm
Min Bend Radius During Installation:	330 mm
Min Bend Radius During Operation:	330 mm

Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
Data Category:	Category 3

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd): 2015-09-01

Part Number

Variants

Item #	Color
NN00101.001000	Gray
NN00101.009999	Gray
NN00101.00500	Gray

Patent: <https://www.belden.com/resources/patents>

History

Revision Number: 2

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.